TECHNICAL DATA SHEET

TDS-HP-EN / SAMPLE 01

Heavy Plank

Engineered European oak. Unfinished for sanding, staining and finishing on site.

3/4" (21 mm)	1/4" (6 mm)	5/8" (15 mm)
Total construction	Sawn oak top layer	Birch plywood core
Nominal	Approximate inch size	Approximate inch size

PRODUCT SPECIFICATION

Construction	Sawn European oak on cross-banded birch plywood.
Format / joint	Plank / tongue and groove.
Widths	5" / 7" / 8-5/8" / 10" (nominal).
Lengths	Random lengths from 2 ft to 10 ft.
Surface	Unfinished. Sand, stain and finish on site.
Grades	Prime / Nature / Classic.

OAK CHARACTER

Prime

Even colour. No sapwood or cracks. Pin knots up to 3/8" (8 mm).

Nature

Approx. 70% Prime boards. Sound knots up to 1-3/8" (approx. 30 mm) on at most 30% of boards. No black knots or filler.

Classic

Sound knots up to 2" (50 mm); black or filled knots up to 1" (25 mm); end cracks up to 4" (100 mm). No sapwood.

Imperial sizes are nominal or approximate. Confirm production dimensions, grade and length distribution for the order.

info@silven.eu

+370 674 55628 / silven.eu